


## RAD-5066-HD/10XX

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your RAD-5066-HD/10XX today!



### Performance Specifications

Travel Rate [in/min]	23
Dynamic Capacity [lb]	7500
Rated Life [in]	5600000
Motor Horse Power	1
Maximum Rod Reaction Torque [in-lb]	475
Std. Brake Torque [ft-lb]	6
Approximate Stopping Distance No Load [in]	0.04
Approximate Stopping Distance Full Load [in]	0.02

### Details

Gear Ratio Primary Reduction	6:1
Gear Ratio Secondary Reduction	6:1
Input Turns Per Inch Of Travel	76
Torque To Raise 1 lb. [in-lb]	0.0046
Max Capacity [lb]	10000
Max HP [hp]	1

### Weight

Basic Weight [lb]	77
Per Inch of Travel [lb]	1.92

### Tube Dimensions

L1 Basic Length [in]	15.13
L2 Basic Length [in]	8.88

### NEMA 56C Dimensions

L3 [in]	3.69
L4 [in]	6.50
E [in]	6.69

### NEMA 180TC Dimensions

L3 [in]	-
L4 [in]	-
F [in]	-