Product Specification Sheet

RAD-10046-HD/10XX

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your RAD-10046-HD/10XX today!

2D/3D CAD ONLINE



Performance Specifications	
Travel Rate [in/min]	6
Dynamic Capacity [lb]	17000
Rated Life [in]	150000
Motor Horse Power	1
Maximum Rod Reaction Torque [in-lb]	1571
Std. Brake Torque [ft-lb]	6
Approximate Stopping Distance No Load [in]	0.01
Approximate Stopping Distance Full Load [in]	0.01
Details	
Gear Ratio Primary Reduction	24:1
Gear Ratio Secondary Reduction	6:1
Input Turns Per Inch Of Travel	303.96
Torque To Raise 1 lb. [in-lb]	0.002
Max Capacity [lb]	20000
Max HP [hp]	1
Weight	
Basic Weight [lb]	93
Per Inch of Travel [lb]	1.92
Tube Dimensions	
L1 Basic Length [in]	15.25
L2 Basic Length [in]	8.88
NEMA 56C Dimensions	
L3 [in]	3.69
L4 [in]	7.25
E [in]	6.69
NEMA 180TC Dimensions	
L3 [in]	-
L4 [in]	-
F [in]	-