



## ELZG 60

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your ELZG 60 today!



<b>Details</b>	
Size	60
Belt	5M25
mm/Rev	220
Number of Teeth	44
Pully Diameter [mm]	70.0
<b>Dimensions</b>	
Basic Length L [mm]	365
A [mm]	144
B [mm]	96
C [mm]	88
D [mm]	80
F [mm]	70
G [mm]	-
H [mm]	-
K [mm]	98
MM	-
OO	M8
P [mm]	95
Q [mm]	168
T	M8
X [mm]	49
Y [mm]	46
Shaft Diameter and Length [mm]	18 x 45
Key	6x6x40
<b>Speed</b>	
Speed Maximum [m/s]	5
<b>Forces and Torques</b>	
No-load torque [Nm]	0.6
Tensile force 0.2 sec [N]	1000
Tensile force permanent [N]	900
Fx dynamic [N]	800
Fy dynamic [N]	2000
Fz dynamic [N]	1100
Mx dynamic [Nm]	43
My dynamic [Nm]	70
Mz dynamic [Nm]	100
Fx static [N]	894
Fy static [N]	3000
Fz static [N]	1700
Mx static [Nm]	67
My static [Nm]	90
Mz static [Nm]	120
<b>Geometrical moments of inertia of aluminum profile</b>	
Elastic modulus [N/mm <sup>2</sup> ]	70000
Ix [mm <sup>4</sup> ]	679000
Iy [mm <sup>4</sup> ]	697000
<b>Weight</b>	
Additional Weight per 100 mm [kg]	0.65
Basic Weight [kg]	10.3