

NH65LEA

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NH65LEA today!



| Details | |
|----------------------------------|----------|
| Size [mm] | 65 |
| Dimensions | |
| L1 [mm] | 247 |
| L2 [mm] | 207 |
| L3 [mm] | 110 |
| L4 [mm] | 16 |
| M1 | M16 |
| H3 [mm] | 20 |
| W1 [mm] | 170 |
| W2 [mm] | 142 |
| W3 [mm] | 14 |
| Forces and Torques | |
| Basic Load Ratings C [kN] | 192.11 |
| Basic Load Ratings C [lbf] | 43175 |
| Basic Load Ratings C0 [kN] | 286.15 |
| Basic Load Ratings C0 [lbf] | 64310 |
| Static Moment Ratings-Ma [kN-m] | 7.21 |
| Static Moment Ratings-Ma [lb-in] | 63798 |
| Static Moment Ratings-Mb [kN-m] | 7.21 |
| Static Moment Ratings-Mb [lb-in] | 63798 |
| Static Moment Ratings-Mc [kN-m] | 10.75 |
| Static Moment Ratings-Mc [lb-in] | 95133 |
| Weight | |
| Weight-Block [kg] | 13.10 |
| Grease Fitting | |
| Grease Fitting Part Number | B-PT 1/8 |