


## ActionJac 2.5-BSJ-DC 24:1

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your ActionJac 2.5-BSJ-DC 24:1 today!



### Details

Capacity [Ton]	2.5
Gear Ratio	24:1
Turns of Worm per Inch Travel	96
Torque to Raise 1 lb. [in-lb]	0.0042
Torque to Raise 1 lb. Keyed [in-lb]	0.0046
Lifting Screw Diameter [in]	1.00
Screw Lead [in]	0.250
Root Diameter [in]	0.820
BackDrive Holding Torque [ft-lb]	1.5
Tare Drag Torque [in-lb]	5

### Performance Specifications

Maximum Allowable Input [hp]	0.50
Maximum Input Torque [in-lb]	21
Maximum Worm Speed at Rated Load Non-keyed [rpm]	1800
Maximum Worm Speed at Rated Load Keyed [rpm]	1370
Maximum Load at 1750 RPM Non-keyed [lb]	4287
Maximum Load at 1750 RPM Keyed [lb]	3914
Starting Torque	1.5 x Running Torque

### Weight

Base 0 Travel [lb]	17
Per Inch of Travel [lb]	0.60
Grease [lb]	0.5