ActionJac 5HL-BSJ-DC 6:1

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 5HL-BSJ-DC 6:1 today!

2D/3D CAD ONLINE



Details	
Capacity [Ton]	5
Gear Ratio	6:1
Turns of Worm per Inch Travel	6
Torque to Raise 1 lb. [in-lb]	0.0387
Torque to Raise 1 lb. Keyed [in-lb]	0.0426
Lifting Screw Diameter [in]	1.50
Screw Lead [in]	1.000
Root Diameter [in]	1.140
BackDrive Holding Torque [ft-lb]	30.0
Tare Drag Torque [in-lb]	10
Performance Specifications	
Maximum Allowable Input [hp]	3.00
Maximum Input Torque [in-lb]	387
Maximum Worm Speed at Rated Load Non-keyed [rpm]	488
Maximum Worm Speed at Rated Load Keyed [rpm]	444
Maximum Load at 1750 RPM Non-keyed [lb]	2792
Maximum Load at 1750 RPM Keyed [lb]	2537
Starting Torque	1.5 x Running Torque
Weight	
Base 0 Travel [lb]	35
Per Inch of Travel [lb]	0.60
Grease [lb]	1.0