# ActionJac 5HL-BSJ-DC 6:1

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 5HL-BSJ-DC 6:1 today!

2D/3D CAD ONLINE




| | |
|---|---|
| **Details** | |
| Capacity [Ton] | 5 |
| Gear Ratio | 6:1 |
| Turns of Worm per Inch Travel | 6 |
| Torque to Raise 1 lb. [in-lb] | 0.0387 |
| Torque to Raise 1 lb. Keyed [in-lb] | 0.0426 |
| Lifting Screw Diameter [in] | 1.50 |
| Screw Lead [in] | 1.000 |
| Root Diameter [in] | 1.140 |
| BackDrive Holding Torque [ft-lb] | 30.0 |
| Tare Drag Torque [in-lb] | 10 |
| **Performance Specifications** | |
| Maximum Allowable Input [hp] | 3.00 |
| Maximum Input Torque [in-lb] | 387 |
| Maximum Worm Speed at Rated Load Non-keyed [rpm] | 488 |
| Maximum Worm Speed at Rated Load Keyed [rpm] | 444 |
| Maximum Load at 1750 RPM Non-keyed [lb] | 2792 |
| Maximum Load at 1750 RPM Keyed [lb] | 2537 |
| Starting Torque | 1.5 x Running Torque |
| **Weight** | |
| Base 0 Travel [lb] | 35 |
| Per Inch of Travel [lb] | 0.60 |
| Grease [lb] | 1.0 |