
## **Product Specification Sheet**



## ActionJac 0.5-BSJ-IK 20:1

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 0.5-BSJ-IK 20:1 today!





Top Plate (optional): 9000-00-12


1<sup>1</sup>/<sub>2</sub> B.C.

Ø 9/2 4 Holes

 $\emptyset 2\frac{1}{4}$ 

3-24 UNF-2B

03



3-24 UNF-2B



Details	
Capacity [Ton]	0.5
Gear Ratio	20:1
Turns of Worm per Inch Travel	100
Torque to Raise 1 lb. [in-lb]	0.0044
Lifting Screw Diameter [in]	0.63
Screw Lead [in]	0.200
Root Diameter [in]	0.500
BackDrive Holding Torque [ft-lb]	0.3
Tare Drag Torque [in-lb]	1
Performance Specifications	
Maximum Allowable Input [hp]	0.17
Maximum Input Torque [in-lb]	4
Maximum Worm Speed at Rated Load [rpm]	1800
Maximum Load at 1750 RPM [lb]	1000
Starting Torque	1.5 x Running Torque
Weight	
Base 0 Travel [lb]	3
Per Inch of Travel [lb]	0.03
Grease [lb]	0.6

 $\emptyset \frac{3}{4}$