
Product Specification Sheet



ActionJac 3-BSJ-UK 6:1

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 3-BSJ-UK 6:1 today!





5 8 - 18 UNF-2B

 $+ \phi_1 \frac{1}{2}$


15

D

Top Plate (optional): 9000-00-01

3 B.C.

- Ø¹³/₃₂ 4 Holes



5 8-18 UNF-2B



Details	
Capacity [Ton]	3
Gear Ratio	6:1
Turns of Worm per Inch Travel	14.53
Torque to Raise 1 lb. [in-lb]	0.0184
Lifting Screw Diameter [in]	1.17
Screw Lead [in]	0.413
Root Diameter [in]	0.870
BackDrive Holding Torque [ft-lb]	6
Tare Drag Torque [in-lb]	6
Performance Specifications	
Maximum Allowable Input [hp]	2.00
Maximum Input Torque [in-lb]	100
Maximum Worm Speed at Rated Load [rpm]	1142
Maximum Load at 1750 RPM [lb]	3914
Starting Torque	1.5 x Running Torque
Weight	
Base 0 Travel [lb]	18.5
Per Inch of Travel [lb]	0.60
Grease [lb]	0.5

→ Ø 1¹/₂