





Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 5-BSJ-U 6:1 today!



Technical drawing of a 3-hole circular plate. The front view (top) shows a circle with three holes. The outer diameter is $\varnothing 4 \frac{1}{2}$. The distance between the centers of the holes is $\varnothing 1 \frac{1}{4}$. The diameter of each hole is $\varnothing \frac{11}{16}$. The side view (bottom) shows the thickness of the plate is $\frac{5}{8}$. The total height of the plate is $1 \frac{13}{16}$. The holes are labeled "3 B.C." and "4 Holes". The thread specification is "1-12 UNF-2B".

Capacity [Ton]	5
Gear Ratio	6:1
Turns of Worm per Inch Travel	12.66
Torque to Raise 1 lb. [in-lb]	0.0183
Lifting Screw Diameter [in]	1.50
Screw Lead [in]	0.473
Root Diameter [in]	1.140
BackDrive Holding Torque [ft-lb]	14
Tare Drag Torque [in-lb]	10

Maximum Allowable Input [hp]	3.00
Maximum Input Torque [in-lb]	183
Maximum Worm Speed at Rated Load [rpm]	1033
Maximum Load at 1750 RPM [lb]	5904
Starting Torque	1.5 x Running Torque

Base 0 Travel [lb]	35
Per Inch of Travel [lb]	0.60
Grease [lb]	1.0