
## **Product Specification Sheet**



## ActionJac 10HL-BSJ-U 24:1

## Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 10HL-BSJ-U 24:1 today!





4<sup>1</sup>/<sub>8</sub>B.C.

Ø 13 16 4 Holes


5<u>3</u> D

#

1-12 UNF-2B

ø 2

13



 $\begin{vmatrix} 2\frac{1}{2}\\ 4\frac{3}{4} \end{vmatrix}$ 

Ø <u>1.000</u> 1.010

1-12 UNF-2B



Details	
Capacity [Ton]	10
Gear Ratio	24:1
Turns of Worm per Inch Travel	24
Torque to Raise 1 lb. [in-lb]	0.0162
Lifting Screw Diameter [in]	1.50
Screw Lead [in]	1.000
Root Diameter [in]	1.140
BackDrive Holding Torque [ft-lb]	6
Tare Drag Torque [in-lb]	20
Performance Specifications	
Maximum Allowable Input [hp]	1.50
Maximum Input Torque [in-lb]	323
Maximum Worm Speed at Rated Load [rpm]	293
Maximum Load at 1750 RPM [lb]	3334
Starting Torque	1.5 x Running Torque
Weight	
Base 0 Travel [lb]	50
Per Inch of Travel [lb]	0.80
Grease [lb]	1.5

+ 1<sup>1</sup>/<sub>4</sub> |∗

Ø2 -

-

 $1\frac{1}{4}$