
## **Product Specification Sheet**

## NOOK

## ActionJac 35AB-MSJ-I 10 2/3:1

## Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 35AB-MSJ-I 10 2/3:1 today!






Ø10 1/2

Ø15 4 Holes 1 1 +

3-12 UN-2B

Ø4

+-2<sup>5</sup>/16



Clevis End (optional): 9001-00-16

Ø<u>1.531</u> 1.541

3-12 UN-2B

+ 27

Ø4



Details	
Capacity [Ton]	35
Gear Ratio	10 2/3:1
Turns of Worm per Inch Travel	16
Torque to Raise 1 lb. [in-lb]	0.0493
Lifting Screw Diameter [in]	3.75
Screw Lead [in]	0.667
Root Diameter [in]	3.009
Tare Drag Torque [in-lb]	50
Performance Specifications	
Maximum Allowable Input [hp]	11.00
Maximum Input Torque [in-lb]	3450
Maximum Worm Speed at Rated Load [rpm]	200
Maximum Load at 1750 RPM [lb]	8035
Starting Torque	2 x Running Torque
Weight	
Base 0 Travel [lb]	145
Per Inch of Travel [lb]	3.40
Grease [lb]	3.5