


Product Specification Sheet

ActionJac 30AB-MSJ-U 10 2/3:1

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 30AB-MSJ-U 10 2/3:1 today!





6 B.C.


 $\emptyset_{1_{\overline{16}}}^{1} 4 \text{ Holes } \frac{3}{4} \xrightarrow{3}$

 $\emptyset 8\frac{1}{2}$

- 25

2 ¹/₄ -12 UN-2B

Ø31/2



415

81/2

1.750 1.760 D

2 4 -12 UN-2B



Details	
Capacity [Ton]	30
Gear Ratio	10 2/3:1
Turns of Worm per Inch Travel	16
Torque to Raise 1 lb. [in-lb]	0.0452
Lifting Screw Diameter [in]	3.38
Screw Lead [in]	0.667
Root Diameter [in]	2.652
Tare Drag Torque [in-lb]	50
Performance Specifications	
Maximum Allowable Input [hp]	11.00
Maximum Input Torque [in-lb]	2710
Maximum Worm Speed at Rated Load [rpm]	256
Maximum Load at 1750 RPM [lb]	8764
Starting Torque	2 x Running Torque
Weight	
Base 0 Travel [lb]	145
Per Inch of Travel [lb]	2.90
Grease [lb]	1.5

 $2\frac{1}{2}$

3 1 D