


Bronze Acme Nut 1"-5 RH

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your Bronze Acme Nut 1"-5 RH today!



| | |
|-----------------------------------|----------|
| Product Info | |
| Part Number | 20105 |
| Thread Direction | RH |
| Type | Bronze |
| Details | |
| Lead [in] | 0.200 |
| Starts | 1 |
| Pitch [in] | 0.200 |
| Turns Per Inch | 5 |
| Lash (Maximum Axial) [in] | 0.009 |
| Nominal Rod Diameter [in] | 1.000 |
| Threads per Inch | 5 |
| Thread Code | 105 |
| Form | 2C |
| Dimensions | |
| B [in] | 1.50 |
| C [in] | 1.50 |
| E [in] | 0.50 |
| F (n) Dia. [in] | (4) .266 |
| F BCD [in] | 2.260 |
| G [in] | 0.52 |
| H [in] | 2.76 |
| J [in] | 1.375-16 |
| Forces and Torques | |
| Torque to Raise 1 lb. [in-lb] | 0.094 |
| Flange Part Numbers | |
| Flange No-Lash Part Number | 73275 |
| Flange Part Number | FLG8281 |
| Weight | |
| Flange Weight [lb] | 0.85 |
| Nut Weight [lb] | 0.50 |
| Performance Specifications | |
| Efficiency [%] | 34 |
| Lead Accuracy +/- [in/in] | 0.0003 |
| Dynamic Load Capacity [lb] | 5000 |
| Static Load Capacity [lb] | 16000 |