


Bronze Acme Nut 2"-5 RH

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your Bronze Acme Nut 2"-5 RH today!



| | |
|-----------------------------------|----------|
| Product Info | |
| Part Number | 20205 |
| Thread Direction | RH |
| Type | Bronze |
| Details | |
| Lead [in] | 0.200 |
| Starts | 1 |
| Pitch [in] | 0.200 |
| Turns Per Inch | 5 |
| Lash (Maximum Axial) [in] | 0.011 |
| Nominal Rod Diameter [in] | 2.000 |
| Threads per Inch | 5 |
| Thread Code | 205 |
| Form | 2C |
| Dimensions | |
| B [in] | 2.75 |
| C [in] | 2.75 |
| E [in] | 0.88 |
| F (n) Dia. [in] | (4) .531 |
| F BCD [in] | 4.062 |
| G [in] | 0.90 |
| H [in] | 4.94 |
| J [in] | 2.548-18 |
| Forces and Torques | |
| Torque to Raise 1 lb. [in-lb] | 0.159 |
| Flange Part Numbers | |
| Flange No-Lash Part Number | 73500 |
| Flange Part Number | FLG7573 |
| Weight | |
| Flange Weight [lb] | 4.73 |
| Nut Weight [lb] | 2.53 |
| Performance Specifications | |
| Efficiency [%] | 20 |
| Lead Accuracy +/- [in/in] | 0.0003 |
| Dynamic Load Capacity [lb] | 20000 |
| Static Load Capacity [lb] | 64000 |