


## PowerTrac XPR 1250 - 0200 RH

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerTrac XPR 1250 - 0200 RH today!







| Screw Code         1250-0200 XPR RA           Precision         XPR           Screw Material         4150           Thread Direction         RH           Details           Ball Circle Diameter [in]         1.250           Lead [in]         0.200           Root Diameter [in]         1.115           End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]         25           End Code for Type 4 [* Journals may show tracings of the thread]         16           Performance Specifications           Lead Accuracy +/- [in./ft.]         0.0010           Part Numbers           2 ft. Part Number         0.0010 |  |
|---|--|
| Screw Material 4150 Thread Direction RH  Details  Ball Circle Diameter [in] 1.250 Lead [in] 0.200 Root Diameter [in] 1.115 End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] 25 End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers  |  |
| Thread Direction RH  Details  Ball Circle Diameter [in] 1.250  Lead [in] 0.200  Root Diameter [in] 1.115  End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] 25  End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications  Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers   |  |
| Details  Ball Circle Diameter [in] 1.250  Lead [in] 0.200  Root Diameter [in] 1.115  End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] 25  End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications  Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers  |  |
| Ball Circle Diameter [in] 1.250 Lead [in] 0.200 Root Diameter [in] 1.115 End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] 25 End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers  |  |
| Lead [in] 0.200  Root Diameter [in] 1.115  End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] 25  End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications  Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers  |  |
| Lead [in] 0.200  Root Diameter [in] 1.115  End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] 25  End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications  Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers  |  |
| End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] 25 End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers   |  |
| End Code for Type 4 [* Journals may show tracings of the thread] 16  Performance Specifications  Lead Accuracy +/- [in./ft.] 0.0010  Part Numbers   |  |
| Performance Specifications Lead Accuracy +/- [in./ft.] 0.0010 Part Numbers  |  |
| Lead Accuracy +/- [in./ft.] 0.0010 Part Numbers   |  |
| Part Numbers  |  |
|   |  |
| 2 ft Part Number  |  |
| Z II. FAIT NUMBE  |  |
| 4 ft. Part Number   |  |
| 6 ft. Part Number XPR12520R72   |  |
| 8 ft. Part Number   |  |
| 12 ft. Part Number XPR12520R144   |  |
| 16 ft. Part Number  |  |
| 20 ft. Part Number  |  |
| Weight  |  |
| Screw Weight [lb./ft.] 3.70   |  |