


PowerAC 1 3/4"-4 LA w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 1 3/4"-4 LA w/Bronze Nut today!







001-	47414
Screw Code	174-LA
Thread Direction	LH
Screw Material	4140 Series
Details	
Lead [in]	0.250
Starts	1
Pitch [in]	0.250
Turns Per Inch	4
Threads per Inch	4
Thread Code	174
Form	2C
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	35
End Code for Type 4 [* Journals may show tracings of the thread]	19
Dimensions	
A - Root Diameter Minimum [in]	1.427
D - Nominal Rod Diameter [in]	1.750
Part Numbers	1.1.00
3 ft. Part Number	51174
6 ft. Part Number	52174
12 ft. Part Number	53174
20 ft. Part Number	JJ 174
Performance Specifications	
	0.0003
Lead Accuracy +/- [in/in]	0.0003
Weight Serou Weight [lb. /ft]	6.07
Screw Weight [lb./ft.]	6.97
ch Acme Nut with Optional Flange	
Product Info	20.17
Part Number	80174
Thread Direction	LH
Type	Bronze
Details	
Lead [in]	0.250
Starts	1
Pitch [in]	0.250
Turns Per Inch	4
Lash (Maximum Axial) [in]	0.011
Nominal Rod Diameter [in]	1.750
Threads per Inch	4
Thread Code	174
Form	2C
Dimensions	
B [in]	2.50
C [in]	2.75
E [in]	0.88
F (n) Dia. [in]	(4) .531
F BCD [in]	4.062
	0.90
G [in]	
H [in]	4.94
J [in]	2.548-18
Forces and Torques	0.450
Torque to Raise 1 lb. [in-lb]	0.153
Flange Part Numbers	
Flange No-Lash Part Number	73500
Flange Part Number	FLG7573
Weight	
Flange Weight [lb]	4.73
Nut Weight [lb]	3.05

Efficiency [%]	26
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	15312
Static Load Capacity [lb]	49900