


PowerAC 1/2"-2 RS w/Plastic Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 1/2"-2 RS w/Plastic Nut today!



Rolled Inch Acme Screw

Product Info

| | |
|------------------|----------------------|
| Screw Code | 052-RS |
| Thread Direction | RH |
| Screw Material | 300 Series Stainless |

Details

| | |
|---|-------|
| Lead [in] | 0.500 |
| Starts | 5 |
| Pitch [in] | 0.100 |
| Turns Per Inch | 2 |
| Threads per Inch | 10 |
| Thread Code | 052 |
| Form | Stub |
| End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] | 10 |
| End Code for Type 4 [* Journals may show tracings of the thread] | 6 |

Dimensions

| | |
|--------------------------------|-------|
| A - Root Diameter Minimum [in] | 0.406 |
| D - Nominal Rod Diameter [in] | 0.500 |

Part Numbers

| | |
|--------------------|-------|
| 3 ft. Part Number | 91052 |
| 6 ft. Part Number | 92052 |
| 12 ft. Part Number | 93052 |
| 20 ft. Part Number | |

Performance Specifications

| | |
|---------------------------|--------|
| Lead Accuracy +/- [in/in] | 0.0003 |
|---------------------------|--------|

Weight

| | |
|------------------------|------|
| Screw Weight [lb./ft.] | 0.53 |
|------------------------|------|

Inch Acme Nut with Optional Flange

Product Info

| | |
|------------------|---------|
| Part Number | 30052 |
| Thread Direction | RH |
| Type | Plastic |

Details

| | |
|---------------------------|-------|
| Lead [in] | 0.500 |
| Starts | 5 |
| Pitch [in] | 0.100 |
| Turns Per Inch | 2 |
| Lash (Maximum Axial) [in] | 0.006 |
| Nominal Rod Diameter [in] | 0.500 |
| Threads per Inch | 10 |
| Thread Code | 052 |
| Form | Stub |

Dimensions

| | |
|-----------------|----------|
| B [in] | 0.75 |
| C [in] | 1.12 |
| E [in] | 0.50 |
| F (n) Dia. [in] | (4) .266 |
| F BCD [in] | 2.090 |
| G [in] | 0.53 |
| H [in] | 2.60 |
| J [in] | .937-16 |

Forces and Torques

| | |
|-------------------------------|-------|
| Torque to Raise 1 lb. [in-lb] | 0.107 |
|-------------------------------|-------|

Flange Part Numbers

| | |
|----------------------------|---------|
| Flange No-Lash Part Number | |
| Flange Part Number | FLG7570 |

Weight

| | |
|--------------------|------|
| Flange Weight [lb] | 0.77 |
| Nut Weight [lb] | 0.03 |

Performance Specifications

| | |
|----------------------------|--------|
| Efficiency [%] | 75 |
| Lead Accuracy +/- [in/in] | 0.0003 |
| Dynamic Load Capacity [lb] | 625 |
| Static Load Capacity [lb] | 625 |