



PowerAC 3/8"-12 RA w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 3/8"-12 RA w/Bronze Nut today!



Rolled Inch Acme Screw

Product Info

Screw Code	032-RA
Thread Direction	RH
Screw Material	4140 Series

Details

Lead [in]	0.083
Starts	1
Pitch [in]	0.083
Turns Per Inch	12
Threads per Inch	12
Thread Code	032
Form	2C
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	7*
End Code for Type 4 [* Journals may show tracings of the thread]	4

Dimensions

A - Root Diameter Minimum [in]	0.263
D - Nominal Rod Diameter [in]	0.375

Part Numbers

3 ft. Part Number	11032
6 ft. Part Number	12032
12 ft. Part Number	
20 ft. Part Number	

Performance Specifications

Lead Accuracy +/- [in/in]	0.0003
---------------------------	--------

Weight

Screw Weight [lb./ft.]	0.29
------------------------	------

Inch Acme Nut with Optional Flange

Product Info

Part Number	20032
Thread Direction	RH
Type	Bronze

Details

Lead [in]	0.083
Starts	1
Pitch [in]	0.083
Turns Per Inch	12
Lash (Maximum Axial) [in]	0.006
Nominal Rod Diameter [in]	0.375
Threads per Inch	12
Thread Code	032
Form	2C

Dimensions

B [in]	0.62
C [in]	0.68
E [in]	0.38
F (n) Dia. [in]	(4) .266
F BCD [in]	1.250
G [in]	0.41
H [in]	1.61
J [in]	.562-18

Forces and Torques

Torque to Raise 1 lb. [in-lb]	0.036
-------------------------------	-------

Flange Part Numbers

Flange No-Lash Part Number	
Flange Part Number	70160

Weight

Flange Weight [lb]	0.23
Nut Weight [lb]	0.05

Performance Specifications

Efficiency [%]	37
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	703
Static Load Capacity [lb]	2250