


## PowerAC Trapezoidal Assembly 900 RS w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC Trapezoidal Assembly 900 RS w/Bronze Nut







Trapezoidal Lead Screw	
Product Info	
Screw Code	900 RS
Screw Material	300 Series Stainless
Thread Direction	RH
Details	
Diameter	10
Lead	3
Starts	2
Pitch [mm]	1.5
Lead Accuracy +/- [*MU*m/25mm]	6.25
Thread Code	900
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	7
End Code for Types 1,2,3,3 [ Sournals may show tracings of the thread]	4
Dimensions	4
A - Root Diameter Mmmimum [mm]	7.92
D - Nominal Rod Diameter	10
Part Numbers	IU
1800 mm Part Number	55900
3600 mm Part Number	20800
	E4000
900 mm Part Number	54900
Weight	0.5
Weight Per Meter [kg]	0.5
Trapezoidal Lead Nut	
Product Info	
Part Number	20900
Thread Direction	RH
Type	Bronze
Details	
Diameter	10
Lead [mm]	3
Starts	2
Pitch [mm]	1.5
Lash (Maximum Axial in) [mm]	0.13
Nominal Rod Diameter	10
Thread Code	900
Dimensions	
B [mm]	16.0
C [mm]	18.0
E [mm]	10.00
F (n) Dia. [mm]	(4) 7.00
F BCD [mm]	25.50
G [mm]	11.0
H [mm]	42.0
J [mm]	M15x1
Forces and Torques	MIONI
Torque to Raise 1 kN [Nm]	1.090
Flange Part Numbers	1.000
Flange Part Number	72001
Weight	12001
Flange Weight [kg]	0.09
Nut Weight [g] Performance Specifications	25
renormance opecinications	
	4.4
Efficiency [%]	44
Efficiency [%] Lead Accuracy +/- [*MU*m/25mm]	6.25
Efficiency [%]	