

NU20SER Assembly

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NU20SER Assembly today!



| | |
|---|-----------|
| Dimensions | |
| H [mm] | 28 |
| H1 [mm] | 4 |
| N [mm] | 11.0 |
| Metric Profile Rail | |
| Details | |
| Size [mm] | 20 |
| Type | Compact |
| Dimensions | |
| d2 [mm] | 9.5 |
| d3 [mm] | 6 |
| h [mm] | 12 |
| H4 [mm] | 19.5 |
| F [mm] | 60 |
| W [mm] | 20 |
| Maximum Length [mm] | 3000 |
| Weight | |
| Weights-Rail [kg/m] | 2.5 |
| Metric Runner Block, Medium Load, Compact Type, 2 Tapped Holes | |
| Details | |
| Size [mm] | 20 |
| Dimensions | |
| L1 [mm] | 52 |
| L2 [mm] | 30 |
| L4 [mm] | 0 |
| M1 x l | M5X7 |
| H3 [mm] | 7.5 |
| W1 [mm] | 42 |
| W2 [mm] | 32 |
| W3 [mm] | 5 |
| Forces and Torques | |
| Basic Load Ratings C [kN] | 9.12 |
| Basic Load Ratings C [lbf] | 2050 |
| Basic Load Ratings C0 [kN] | 12.94 |
| Basic Load Ratings C0 [lbf] | 2909 |
| Static Moment Ratings-Ma [kN-m] | 0.05 |
| Static Moment Ratings-Ma [lb-in] | 434 |
| Static Moment Ratings-Mb [kN-m] | 0.05 |
| Static Moment Ratings-Mb [lb-in] | 434 |
| Static Moment Ratings-Mc [kN-m] | 0.15 |
| Static Moment Ratings-Mc [lb-in] | 1302 |
| Weight | |
| Weight-Block [kg] | 0.16 |
| Grease Fitting | |
| Grease Fitting Part Number | NAS516-1A |