

NU35ER Assembly

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NU35ER Assembly today!



| | |
|--|---------|
| Dimensions | |
| H [mm] | 48 |
| H1 [mm] | 8 |
| N [mm] | 18.0 |
| Metric Profile Rail | |
| Details | |
| Size [mm] | 35 |
| Type | Compact |
| Dimensions | |
| d2 [mm] | 14 |
| d3 [mm] | 9 |
| h [mm] | 15 |
| H4 [mm] | 32 |
| F [mm] | 80 |
| W [mm] | 34 |
| Maximum Length [mm] | 3000 |
| Weight | |
| Weights-Rail [kg/m] | 7.5 |
| Metric Runner Block, Heavy Load, Compact Type, 4 Tapped Holes | |
| Details | |
| Size [mm] | 35 |
| Dimensions | |
| L1 [mm] | 112 |
| L2 [mm] | 80 |
| L3 [mm] | 50 |
| L4 [mm] | 12 |
| H3 [mm] | 10 |
| M1 x l | M8X12 |
| W1 [mm] | 70 |
| W2 [mm] | 50 |
| W3 [mm] | 10 |
| Forces and Torques | |
| Basic Load Ratings C [kN] | 37.55 |
| Basic Load Ratings C [lbf] | 8441 |
| Basic Load Ratings C0 [kN] | 62.55 |
| Basic Load Ratings C0 [lbf] | 14061 |
| Static Moment Ratings-Ma [kN-m] | 0.64 |
| Static Moment Ratings-Ma [lb-in] | 5642 |
| Static Moment Ratings-Mb [kN-m] | 0.64 |
| Static Moment Ratings-Mb [lb-in] | 5642 |
| Static Moment Ratings-Mc [kN-m] | 1.13 |
| Static Moment Ratings-Mc [lb-in] | 9982 |
| Weight | |
| Weight-Block [kg] | 1.30 |
| Grease Fitting | |
| Grease Fitting Part Number | B-M6F |