


PowerAC 1"-1 TA w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 1"-1 TA w/Bronze Nut today!



Rolled Inch Twin-Lead Acme Screw

Product Info

Screw Code	111 TA
Screw Direction	RH/LH
Screw Material	4140 Series

Details

Lead [in]	1.000
Starts	10
Pitch [in]	0.100
Turns Per Inch	1
Threads per Inch	10
Thread Code	111
Form	Stub
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	20
End Code for Type 4 [* Journals may show tracings of the thread]	12

Dimensions

A - Root Diameter Minimum [in]	0.906
D - Nominal Rod Diameter [in]	1.000
Incomplete Overlapping Thread Length [in]	2.00
Maximum Overall Length [in]	72
Maximum Useable LH & RH Thread [in]	35.00

Weight

Weight Per Foot [lb]	2.38
----------------------	------

Part Numbers

36" Part Number	
72" Part Number	
144" Part Number	

Performance Specifications

Lead Accuracy +/- [in/in]	0.0003
---------------------------	--------

Inch Acme Nut with Optional Flange

Product Info

Part Number	80111
Thread Direction	LH
Type	Bronze

Details

Lead [in]	1.000
Starts	10
Pitch [in]	0.100
Turns Per Inch	1
Lash (Maximum Axial) [in]	0.008
Nominal Rod Diameter [in]	1.000
Threads per Inch	10
Thread Code	111
Form	Stub

Dimensions

B [in]	1.50
C [in]	1.50
E [in]	0.50
F (n) Dia. [in]	(4) .266
F BCD [in]	2.260
G [in]	0.52
H [in]	2.76
J [in]	1.375-16

Forces and Torques

Torque to Raise 1 lb. [in-lb]	0.231
-------------------------------	-------

Flange Part Numbers

Flange No-Lash Part Number	73275
Flange Part Number	FLG8281

Weight

Flange Weight [lb]	0.85
--------------------	------

Nut Weight [lb]	0.46
Performance Specifications	
Efficiency [%]	69
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	5000
Static Load Capacity [lb]	16000
Inch Acme Nut with Optional Flange	
Product Info	
Part Number	20111
Thread Direction	RH
Type	Bronze
Details	
Lead [in]	1.000
Starts	10
Pitch [in]	0.100
Turns Per Inch	1
Lash (Maximum Axial) [in]	0.008
Nominal Rod Diameter [in]	1.000
Threads per Inch	10
Thread Code	111
Form	Stub
Dimensions	
B [in]	1.50
C [in]	1.50
E [in]	0.50
F (n) Dia. [in]	(4) .266
F BCD [in]	2.260
G [in]	0.52
H [in]	2.76
J [in]	1.375-16
Forces and Torques	
Torque to Raise 1 lb. [in-lb]	0.231
Flange Part Numbers	
Flange No-Lash Part Number	73275
Flange Part Number	FLG8281
Weight	
Flange Weight [lb]	0.85
Nut Weight [lb]	0.46
Performance Specifications	
Efficiency [%]	69
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	5000
Static Load Capacity [lb]	16000