


PowerAC 3/4"-10 TA w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 3/4"-10 TA w/Bronze Nut today!



Rolled Inch Twin-Lead Acme Screw

Product Info

Screw Code	070 TA
Screw Direction	RH/LH
Screw Material	4140 Series

Details

Lead [in]	0.166
Starts	1
Pitch [in]	0.166
Turns Per Inch	10
Threads per Inch	6
Thread Code	086
Form	2C
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	15
End Code for Type 4 [* Journals may show tracings of the thread]	8

Dimensions

A - Root Diameter Minimum [in]	0.608
D - Nominal Rod Diameter [in]	0.750
Incomplete Overlapping Thread Length [in]	2.00
Maximum Overall Length [in]	72
Maximum Useable LH & RH Thread [in]	35.00

Weight

Weight Per Foot [lb]	1.65
----------------------	------

Part Numbers

36" Part Number	TL3/4-10RS 36
72" Part Number	TL3/4-10RS 72
144" Part Number	

Performance Specifications

Lead Accuracy +/- [in/in]	0.0003
---------------------------	--------

Inch Acme Nut with Optional Flange

Product Info

Part Number	80070
Thread Direction	LH
Type	Bronze

Details

Lead [in]	0.100
Starts	1
Pitch [in]	0.100
Turns Per Inch	10
Lash (Maximum Axial) [in]	0.007
Nominal Rod Diameter [in]	0.750
Threads per Inch	10
Thread Code	070
Form	2C

Dimensions

B [in]	1.25
C [in]	1.12
E [in]	0.50
F (n) Dia. [in]	(4) .266
F BCD [in]	2.090
G [in]	0.53
H [in]	2.63
J [in]	1.000-18

Forces and Torques

Torque to Raise 1 lb. [in-lb]	0.064
-------------------------------	-------

Flange Part Numbers

Flange No-Lash Part Number	73262
Flange Part Number	70262

Weight

Flange Weight [lb]	0.78
--------------------	------

Nut Weight [lb]	0.22
Performance Specifications	
Efficiency [%]	25
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	2812
Static Load Capacity [lb]	9000
Inch Acme Nut with Optional Flange	
Product Info	
Part Number	20070
Thread Direction	RH
Type	Bronze
Details	
Lead [in]	0.100
Starts	1
Pitch [in]	0.100
Turns Per Inch	10
Lash (Maximum Axial) [in]	0.007
Nominal Rod Diameter [in]	0.750
Threads per Inch	10
Thread Code	070
Form	2C
Dimensions	
B [in]	1.25
C [in]	1.12
E [in]	0.50
F (n) Dia. [in]	(4) .266
F BCD [in]	2.090
G [in]	0.53
H [in]	2.63
J [in]	1.000-18
Forces and Torques	
Torque to Raise 1 lb. [in-lb]	0.064
Flange Part Numbers	
Flange No-Lash Part Number	73262
Flange Part Number	70262
Weight	
Flange Weight [lb]	0.78
Nut Weight [lb]	0.22
Performance Specifications	
Efficiency [%]	25
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	2812
Static Load Capacity [lb]	9000