



PowerAC 5/8"-2 2/3 TA w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 5/8"-2 2/3 TA w/Bronze Nut today!



Rolled Inch Twin-Lead Acme Screw

Product Info

Screw Code	063 TA
Screw Direction	RH/LH
Screw Material	4140 Series

Details

Lead [in]	0.375
Starts	3
Pitch [in]	0.125
Turns Per Inch	2.66
Threads per Inch	8
Thread Code	063
Form	2C
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	10
End Code for Type 4 [* Journals may show tracings of the thread]	6

Dimensions

A - Root Diameter Minimum [in]	0.457
D - Nominal Rod Diameter [in]	0.625
Incomplete Overlapping Thread Length [in]	2.00
Maximum Overall Length [in]	36
Maximum Useable LH & RH Thread [in]	17.00

Weight

Weight Per Foot [lb]	0.84
----------------------	------

Part Numbers

36" Part Number	
72" Part Number	
144" Part Number	

Performance Specifications

Lead Accuracy +/- [in/in]	0.0003
---------------------------	--------

Inch Acme Nut with Optional Flange

Product Info

Part Number	80063
Thread Direction	LH
Type	Bronze

Details

Lead [in]	0.375
Starts	3
Pitch [in]	0.125
Turns Per Inch	2.67
Lash (Maximum Axial) [in]	0.010
Nominal Rod Diameter [in]	0.625
Threads per Inch	8
Thread Code	063
Form	2C

Dimensions

B [in]	1.00
C [in]	1.12
E [in]	0.50
F (n) Dia. [in]	(4) .266
F BCD [in]	2.090
G [in]	0.53
H [in]	2.60
J [in]	.937-16

Forces and Torques

Torque to Raise 1 lb. [in-lb]	0.100
-------------------------------	-------

Flange Part Numbers

Flange No-Lash Part Number	
Flange Part Number	FLG7570

Weight

Flange Weight [lb]	0.77
--------------------	------

Nut Weight [lb]	0.22
Performance Specifications	
Efficiency [%]	60
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	1953
Static Load Capacity [lb]	6250
Inch Acme Nut with Optional Flange	
Product Info	
Part Number	20063
Thread Direction	RH
Type	Bronze
Details	
Lead [in]	0.375
Starts	3
Pitch [in]	0.125
Turns Per Inch	2.67
Lash (Maximum Axial) [in]	0.010
Nominal Rod Diameter [in]	0.625
Threads per Inch	8
Thread Code	063
Form	2C
Dimensions	
B [in]	1.00
C [in]	1.12
E [in]	0.50
F (n) Dia. [in]	(4) .266
F BCD [in]	2.090
G [in]	0.53
H [in]	2.60
J [in]	.937-16
Forces and Torques	
Torque to Raise 1 lb. [in-lb]	0.100
Flange Part Numbers	
Flange No-Lash Part Number	
Flange Part Number	FLG7570
Weight	
Flange Weight [lb]	0.77
Nut Weight [lb]	0.22
Performance Specifications	
Efficiency [%]	60
Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	1953
Static Load Capacity [lb]	6250