

Product Specification Sheet


PowerTrac 1500 - 0250 SGT RA, with SAG Ball Nut, Adjustable

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerTrac 1500 - 0250 SGT RA, with SAG Ball Nut,



2D/3D CAD
ONLINE





Inch Ball Screw	
(Screw)Product Info	
Screw Code	1500-0250 SGT RA
Precision	SGT
Screw Material	4150
Thread Direction	RH
(Screw)Details	
Ball Circle Diameter [in]	1.500
Lead [in]	0.250
Root Diameter [in]	1.320
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	30
End Code for Type 4 [* Journals may show tracings of the thread]	19
(Screw)Performance Specifications	
Lead Accuracy +/- [in./ft.]	0.0005
(Screw)Part Numbers	
2 ft. Part Number	
4 ft. Part Number	
6 ft. Part Number	GT15025R72
8 ft. Part Number	0110020112
12 ft. Part Number	GT15025R120
16 ft. Part Number	01130231120
20 ft. Part Number	
(Screw)Weight	
Screw Weight [lb./ft.]	5.41
	5.41
Inch Ball Nut, for SGT, Ground Accuracy, Preloaded, Adjustable, SAG	
(Nut)Product Info	04.00705
Ball Nut Number	SAG0705
Thread Direction	RH
(Nut)Details	(
Ball Circle Diameter [in]	1.500
Lead [in]	0.250
Nominal Ball Diameter [in]	0.156
Root diameter [in]	1.320
(Nut)Forces and Torques	
Torque to Raise 1 lb. [in-lb]	0.044
(Nut)Flange Part Numbers	
Flange Part Number	INTEGRAL
(Nut)Wiper Part Numbers	
Wiper Kit Part Number	BRUSH
(Nut)Weight	
Nut Weight [lb]	6.00
(Nut)Performance Specifications	
Maximum Adjustable Preload [lb]	920
Spring Rate x 10 ⁶ [Ib./in.]	
Dynamic Load [lb]	5950
Static Load [lb]	44030
	11 000