DD-256-ML/20XX

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-256-ML/20XX today!

2D/3D CAD ONLINE



Performance Specifications	
Travel Rate [in/min]	144
Dynamic Capacity [lb]	3600
Rated Life [in]	900000
Motor Horse Power [hp]	2
Maximum Rod Reaction Torque [in-lb]	318
Std. Brake Torque [ft-lb]	0.21
Approximate Stopping Distance No Load [in]	0.42
Approximate Stopping Distance Full Load [in]	10.00
Details	
Gear Ratio	6:1
Input Turns Per Inch Of Travel	12
Torque To Raise 1 lb. [in-lb]	0.0201
Max Capacity [lb]	5000
Max HP [hp]	2
Weight	
Basic Weight [lb]	33
Per Inch of Travel [lb]	1.05
Tube Dimensions	
L1 Basic Length [in]	12.44
L2 Basic Length [in]	7.13
NEMA 42 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 48 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 56C Dimensions	
L3 [in]	6.25
E [in]	6.62
F [in]	3.50
NEMA 182TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 184TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 213TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-