# Product Specification Sheet

## DD-10024-HL/15XX

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-10024-HL/15XX today!

2D/3D CAD ONLINE



| | |
|---|---|
| **Performance Specifications** | |
| Travel Rate [in/min] | 72 |
| Dynamic Capacity [lb] | 2700 |
| Rated Life [in] | 22000000 |
| Motor Horse Power [hp] | 1.5 |
| Maximum Rod Reaction Torque [in-lb] | 478 |
| Std. Brake Torque [ft-lb] | 0.15 |
| Approximate Stopping Distance No Load [in] | 0.16 |
| Approximate Stopping Distance Full Load [in] | 6.00 |
| **Details** | |
| Gear Ratio | 24:1 |
| Input Turns Per Inch Of Travel | 24 |
| Torque To Raise 1 lb. [in-lb] | 0.0162 |
| Max Capacity [lb] | 20000 |
| Max HP [hp] | 1.5 |
| **Weight** | |
| Basic Weight [lb] | 80 |
| Per Inch of Travel [lb] | 1.92 |
| **Tube Dimensions** | |
| L1 Basic Length [in] | 15.25 |
| L2 Basic Length [in] | 8.88 |
| **NEMA 42 Dimensions** | |
| L3 [in] | - |
| E [in] | - |
| F [in] | - |
| **NEMA 48 Dimensions** | |
| L3 [in] | - |
| E [in] | - |
| F [in] | - |
| **NEMA 56C Dimensions** | |
| L3 [in] | 8.25 |
| E [in] | 6.75 |
| F [in] | 4.38 |
| **NEMA 182TC Dimensions** | |
| L3 [in] | - |
| E [in] | - |
| F [in] | - |
| **NEMA 184TC Dimensions** | |
| L3 [in] | 9.00 |
| E [in] | 9.25 |
| F [in] | 4.38 |
| **NEMA 213TC Dimensions** | |
| L3 [in] | - |
| E [in] | - |
| F [in] | - |