


PowerTrac 6000 - 1000 SRT RA, with SBN Ball Nut, Internal

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerTrac 6000 - 1000 SRT RA, with SBN Ball Nut, Internal







Inch Ball Screw	
(Screw)Product Info	
Screw Code	6000-1000 SRT RA
Precision	SRT
Screw Material	4150
Thread Direction	RH
(Screw)Details	TOT
Ball Circle Diameter [in]	6.000
Lead [in]	1.000
Root Diameter [in]	5.232
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	n/a
End Code for Types 1,2,3,3 [Journals may show tracings of the thread]	n/a
(Screw)Performance Specifications	ıva
Lead Accuracy +/- [in./ft.]	0.0080
(Screw)Part Numbers	0.0000
2 ft. Part Number	
4 ft. Part Number	
6 ft. Part Number	
8 ft. Part Number	
12 ft. Part Number	
16 ft. Part Number	
20 ft. Part Number	
(Screw)Weight	04.40
Screw Weight [lb./ft.]	34.40
Inch Ball Nut, for SRT, Standard Accuracy, No Preload, SBN, Standard (Nut)Product Info	
Ball Nut Number	SBN10438
Thread Direction	RH
(Nut)Details	TALL
Ball Circle Diameter [in]	6.000
Lead [in]	1.000
Nominal Ball Diameter [in]	1.514
Root diameter [in]	5.232
(Nut)Dimensions	5.232
A [in]	
(Nut)Forces and Torques	0.477
Torque to Raise 1 lb. [in-lb]	0.177
(Nut)Flange Part Numbers	FI 040407
Flange Part Number	FLG10437
(Nut)Wiper Part Numbers	W//D40444
Wiper Kit Part Number	WKP10441
Wiper Kit Felt Part Number	
(Nut)Weight	
Nut Weight [lb]	170.00
(Nut)Performance Specifications	
Lead Accuracy +/- [in./ft.]	0.002
Maximum Adjustable Preload [lb]	
Spring Rate x 10 ⁶ [lb./in.]	
Dynamic Load [lb]	115507
Static Load [lb]	443548