


DD-105-HD

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-105-HD today!



Details

Gear Ratio	5:1
Max Capacity [lb]	2000
Input Turns Per Inch Of Travel	25
Torque To Raise 1 lb. [in-lb]	0.0095
Ball Screw	0750-0200 SRT RA
Screw Lead [in]	0.200
Root Diameter [in]	0.602
Max HP [hp]	0.5

Weight

Basic Weight [lb]	19
Per Inch of Travel [lb]	0.77

Tube Dimensions

L1 Basic Length [in]	10.75
L2 Basic Length [in]	6.38

NEMA 42 Dimensions

L3 [in]	4.48
E [in]	4.63
F [in]	2.69

NEMA 48 Dimensions

L3 [in]	4.48
E [in]	4.63
F [in]	3.12

NEMA 56C Dimensions

L3 [in]	5.71
E [in]	6.63
F [in]	3.75

NEMA 182TC Dimensions

L3 [in]	-
E [in]	-

NEMA 182TC/18TCc Dimensions

F [in]	-
--------	---

NEMA 184TC Dimensions

L3 [in]	-
E [in]	-
F [in]	-

NEMA 213TC Dimensions

L3 [in]	-
E [in]	-
F [in]	-