Product Specification Sheet

DD-1008-SL

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-1008-SL today!



Details	
Gear Ratio	8:1
Max Capacity [lb]	20000
Input Turns Per Inch Of Travel	4.26
Torque To Raise 1 lb. [in-lb]	0.0598
Ball Screw	1500-1875 SRT RA
Screw Lead [in]	1.875
Root Diameter [in]	1.188
Max HP [hp]	5
Weight	
Basic Weight [lb]	80
Per Inch of Travel [lb]	1.92
Tube Dimensions	
L1 Basic Length [in]	15.25
L2 Basic Length [in]	8.88
NEMA 42 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 48 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 56C Dimensions	
L3 [in]	8.25
E [in]	4.38
F [in]	6.75
NEMA 182TC Dimensions	
L3 [in]	9.00
E [in]	9.25
NEMA 182TC/18TCc Dimensions	
F [in]	4.38
NEMA 184TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 213TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-