Product Specification Sheet

DD-20024-HL

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-20024-HL today!

2D/3D CAD ONLINE



Details	
Gear Ratio	24:1
Max Capacity [lb]	40000
Input Turns Per Inch Of Travel	24
Torque To Raise 1 lb. [in-lb]	0.0157
Ball Screw	2250-1000 SRT RA
Screw Lead [in]	1.000
Root Diameter [in]	1.850
Max HP [hp]	2.5
Weight	
Basic Weight [lb]	154
Per Inch of Travel [lb]	3.31
Tube Dimensions	
L1 Basic Length [in]	21.13
L2 Basic Length [in]	12.63
NEMA 42 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 48 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 56C Dimensions	
L3 [in]	8.65
E [in]	6.75
F [in]	5.19
NEMA 182TC Dimensions	
L3 [in]	-
E [in]	-
NEMA 182TC/18TCc Dimensions	
F [in]	-
NEMA 184TC Dimensions	
L3 [in]	9.00
E [in]	9.25
F [in]	5.19
NEMA 213TC Dimensions	
L3 [in]	9.65
E [in]	9.25
F [in]	5.69