Product Specification Sheet

DD-1020-A5

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-1020-A5 today!



Details	
Gear Ratio	20:1
Max Capacity [lb]	2000
Input Turns Per Inch Of Travel	100
Torque To Raise 1 lb. [in-lb]	0.0125
Acme Screw	3/4-5 RA
Screw Lead [in]	0.200
Root Diameter [in]	0.502
Max HP [hp]	0.25
Weight	
Basic Weight [lb]	15
Per Inch of Travel [lb]	0.76
Tube Dimensions	
L1 Basic Length [in]	8.25
L2 Basic Length [in]	4.25
NEMA 42 Dimensions	
L3 [in]	4.48
E [in]	4.63
F [in]	2.69
NEMA 48 Dimensions	
L3 [in]	4.48
E [in]	4.63
F [in]	3.12
NEMA 56C Dimensions	
L3 [in]	5.71
E [in]	6.63
F [in]	3.75
NEMA 182TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 184TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 213TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-