Product Specification Sheet

DD-256-A4

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-256-A4 today!

2D/3D CAD ONLINE



Details	
Gear Ratio	6:1
Max Capacity [lb]	5000
Input Turns Per Inch Of Travel	24
Torque To Raise 1 lb. [in-lb]	0.0252
Acme Screw	1-4 RA
Screw Lead [in]	0.250
Root Diameter [in]	0.698
Max HP [hp]	2
Weight	
Basic Weight [lb]	30
Per Inch of Travel [lb]	1.00
Tube Dimensions	
L1 Basic Length [in]	10.38
L2 Basic Length [in]	4.75
NEMA 42 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 48 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 56C Dimensions	
L3 [in]	6.25
E [in]	6.62
F [in]	3.50
NEMA 182TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 184TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 213TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-