Product Specification Sheet

DD-2008-A3

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your DD-2008-A3 today!

2D/3D CAD ONLINE



Details	
Gear Ratio	8:1
Max Capacity [lb]	40000
Input Turns Per Inch Of Travel	24
Torque To Raise 1 lb. [in-lb]	0.0394
Acme Screw	2 1/2-3 RA
Screw Lead [in]	0.333
Root Diameter [in]	2.106
Max HP [hp]	7.5
Weight	
Basic Weight [lb]	138
Per Inch of Travel [lb]	3.60
Tube Dimensions	
L1 Basic Length [in]	17.44
L2 Basic Length [in]	8.94
NEMA 42 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 48 Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 56C Dimensions	
L3 [in]	8.65
E [in]	6.75
F [in]	5.19
NEMA 182TC Dimensions	
L3 [in]	-
E [in]	-
F [in]	-
NEMA 184TC Dimensions	
L3 [in]	9.00
E [in]	9.25
F [in]	5.18
NEMA 213TC Dimensions	
L3 [in]	9.65
E [in]	9.25
F [in]	5.69