


NMR 12MN ZU Assembly

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NMR 12MN ZU Assembly today!



Dimensions

| | |
|---------------------|-----|
| H [mm] | 13 |
| W ₂ [mm] | 7.5 |

Standard Miniature Block Four Mounting Holes

Details

| | |
|-----------|----|
| Size [mm] | 12 |
|-----------|----|

Dimensions

| | |
|---------------------|----------|
| W [mm] | 27 |
| L [mm] | 35.4 |
| L ₁ [mm] | 22 |
| h ₂ [mm] | 10.2 |
| P ₁ [mm] | 15 |
| P ₂ [mm] | 20 |
| M × g ₂ | M3 × 3.5 |
| ∅ [mm] | 1.3 |
| S [mm] | 3.2 |
| T [mm] | 4.3 |

Forces and Torques

| | |
|--|------|
| Basic Load Ratings C [N] | 2308 |
| Basic Load Ratings C ₀ [N] | 3465 |
| Static Moment Ratings-M _a [N-m] | 12.9 |
| Static Moment Ratings-M _b [N-m] | 12.9 |
| Static Moment Ratings-M _c [N-m] | 21.5 |

Weight

| | |
|------------------|----|
| Weight-Block [g] | 34 |
|------------------|----|

Standard Miniature Rail Top Mount

Details

| | |
|-----------|----|
| Size [mm] | 12 |
|-----------|----|

Dimensions

| | |
|---------------------|-----|
| H [mm] | 13 |
| W ₁ [mm] | 12 |
| H ₁ [mm] | 7.5 |
| P [mm] | 25 |
| D [mm] | 6 |
| d ₁ [mm] | 3.5 |
| g ₁ [mm] | 4.5 |

Weight

| | |
|--------------------|-------|
| Weights-Rail [g/m] | 602.0 |
|--------------------|-------|

Standard Miniature Rail Bottom Tapped Mount

Details

| | |
|-----------|----|
| Size [mm] | 12 |
|-----------|----|

Dimensions

| | |
|---------------------|----------|
| H ₁ [mm] | 7.5 |
| W ₁ [mm] | 12 |
| P [mm] | 25 |
| M ₁ | M4 × 0.7 |

Weight

