


Product Specification Sheet

NMR 5MN ZZ Assembly

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NMR 5MN ZZ Assembly today!






H,







	Optional Bottom Tapped Mount Rail			
H,		P		

Dimensions	
H [mm]	6
W2 [mm]	3.5
Standard Miniature Block Two Perpendiculare Mounting Holes	
(Runner Block)Details	
Size [mm]	5
(Runner Block)Dimensions	v
W [mm]	12
L [mm]	16
L1 [mm]	10
h2 [mm]	4.5
P2 [mm]	8
	о M2 × 1.5
M × g2	
ØS	0.7
S T	1.3
	۷
(Runner Block)Forces and Torques	205
Basic Load Ratings C [N]	335
Basic Load Ratings C0 [N]	550
Static Moment Ratings-Ma [N-m]	1.0
Static Moment Ratings-Mb [N-m]	1.0
Static Moment Ratings-Mc [N-m]	1.7
(Runner Block)Weight	
Weight-Block [g]	3.5
Standard Miniature Rail Top Mount (Top Mount Rail)Details	
Size [mm]	5
(Top Mount Rail)Dimensions	
H [mm]	6
W1 [mm]	5
H1 [mm]	3.5
P [mm]	15
D [mm]	3.5
d1 [mm]	2.4
g1 [mm]	1
(Top Mount Rail)Weight	
Weights-Rail [g/m]	116.0
Standard Miniature Rail Bottom Tapped Mount (Bottom Mount Rail)Details	
Size [mm]	5
(Bottom Mount Rail)Dimensions	
H1 [mm]	3.5
W1 [mm]	5
P [mm]	15
M1	M3 x .05
(Bottom Mount Rail)Weight	
Weights-Rail [g/m]	,