



## NMR 12MN EE Assembly


Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NMR 12MN EE Assembly today!











Dimensions	
H [mm]	13
W2 [mm]	7.5
Standard Miniature Block Four Mounting Holes	
(Runner Block)Details	
Size [mm]	12
(Runner Block)Dimensions	
W [mm]	27
L [mm]	36.8
L1 [mm]	22
h2 [mm]	10.7
P1 [mm]	15
P2 [mm]	20
M × g2	M3 × 3.5
Ø [mm]	1.3
S [mm]	3.2
T [mm]	4.3
(Runner Block)Forces and Torques	
Basic Load Ratings C [N]	2308
Basic Load Ratings C0 [N]	3465
Static Moment Ratings-Ma [N-m]	12.9
Static Moment Ratings-Mb [N-m]	12.9
Static Moment Ratings-Mc [N-m]	21.5
(Runner Block)Weight	
Weight-Block [g]	34
Standard Miniature Rail Top Mount	
(Top Mount Rail)Details	
Size [mm]	12
(Top Mount Rail)Dimensions	
H [mm]	13
W1 [mm]	12
H1 [mm]	7.5
P [mm]	25
D [mm]	6
d1 [mm]	3.5
g1 [mm]	4.5
(Top Mount Rail)Weight	
Weights-Rail [g/m]	602.0
Standard Miniature Rail Bottom Tapped Mount	
(Bottom Mount Rail)Details Size [mm]	12
(Bottom Mount Rail)Dimensions	1Z 
	7.5
H1 [mm] W1 [mm]	7.5 12
	25
P [mm] M1	25 M4 x 0.7
****	IVI4 X U.7
(Bottom Mount Rail)Weight	000.0
Weights-Rail [g/m]	602.0