




## NARC 15 MS

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your NARC 15 MS today!



|                                |          |
|--------------------------------|----------|
| <b>Details</b>                 |          |
| Size [mm]                      | 15       |
| <b>Dimensions</b>              |          |
| W [mm]                         | 34       |
| L [mm]                         | 40.4     |
| L1 [mm]                        | 26       |
| h2 [mm]                        | 20.7     |
| P2 [mm]                        | 26       |
| M1 [mm]                        | -        |
| M x g2                         | M4 x 7   |
| T [mm]                         | 6        |
| N1                             | M3 x 6.5 |
| N2                             | M3 x 6   |
| N3 [O-Ring Seal]               | P3       |
| E [mm]                         | 4.5      |
| S1 [mm]                        | 4.5      |
| S2 [mm]                        | 7.5      |
| S3 [mm]                        | 15.7     |
| S4 [mm]                        | 16.8     |
| <b>Forces and Torques</b>      |          |
| Basic Load Ratings C [kN]      | 7.7      |
| Basic Load Ratings C0 [kN]     | 12.1     |
| Static Moment Ratings-Ma [N-m] | 50.0     |
| Static Moment Ratings-Mb [N-m] | 50.0     |
| Static Moment Ratings-Mc [N-m] | 100.0    |
| <b>Weight</b>                  |          |
| Weight-Block [g]               | 96       |