


NHRC 15 MN Assembly

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NHRC 15 MN Assembly today!



Dimensions	
H [mm]	28
W2 [mm]	9.5
Standard Caged Ball Block Four Mounting Holes	
Details	
Size [mm]	15
Dimensions	
W [mm]	34
L [mm]	55.9
L1 [mm]	40.3
h2 [mm]	34.7
P1 [mm]	26
P2 [mm]	26
M1 [mm]	—
M x g2	M4 x 7
T [mm]	6
N1	M3 x 6.5
N2	M3 x 6
N3 [O-Ring Seal]	P3
E [mm]	3.5
S1 [mm]	8.5
S2 [mm]	11.5
S3 [mm]	9.8
S4 [mm]	10.9
Forces and Torques	
Basic Load Ratings C [kN]	9.9
Basic Load Ratings C0 [kN]	17.5
Static Moment Ratings-Ma [N-m]	105.0
Static Moment Ratings-Mb [N-m]	105.0
Static Moment Ratings-Mc [N-m]	140.0
Weight	
Weight-Block [g]	184
Caged Ball Rail Top Mount	
Details	
Size [mm]	15
Dimensions	
W1 [mm]	15
H1 [mm]	15
P [mm]	60
D [mm]	7.5
d1 [mm]	4.5
g1 [mm]	5.3
Weight	
Weights-Rail [g/m]	1290.0
Caged Ball Rail Bottom Tapped Mount	
Details	
Size [mm]	15
Dimensions	
W1 [mm]	15
H1 [mm]	15
P [mm]	60
M x g3	M5 x 8
Weight	
Weights-Rail [g/m]	1290.0