

GRV03 - 225 - S

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your GRV03 - 225 - S today!



| | |
|-----------------------------------|-----------------|
| Product Info | |
| Part Number | GRV03 - 225 - S |
| Max Stroke [mm] | 184 |
| Material Specification | |
| Rail | SUS440C + Ni |
| Roller | 100Cr6 |
| Retainer | SUS304 |
| Dimensions | |
| H [mm] | 18 |
| T [mm] | 8 |
| W [mm] | 8.3 |
| L [mm] | 225 |
| n [mm] | 18 |
| P [mm] | 25 |
| L1 [mm] | 12.5 |
| L2 [mm] | 0.8 |
| ØD [mm] | 3 |
| L3 [mm] | 136.4 |
| R [mm] | 27 |
| P1 [mm] | 3.2 |
| P2 [mm] | 5 |
| A [mm] | 3.5 |
| M | M4 |
| d1 [mm] | 3.3 |
| d2 [mm] | 6 |
| B [mm] | 3.1 |
| Performance Specifications | |
| Dynamic C [N] | 638 |
| Static C0 [N] | 761 |
| Capacity Per Bearing [N] | 254 |
| Weight | |
| Per Rail [g] | 215 |