

GRV12 - 600 - S

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your GRV12 - 600 - S today!



| | |
|-----------------------------------|-----------------|
| Product Info | |
| Part Number | GRV12 - 600 - S |
| Max Stroke [mm] | 492 |
| Material Specification | |
| Rail | SUS440C + Ni |
| Roller | 100Cr6 |
| Retainer | SUS304 |
| Dimensions | |
| H [mm] | 58 |
| T [mm] | 28 |
| W [mm] | 26.9 |
| L [mm] | 600 |
| n [mm] | 12 |
| P [mm] | 100 |
| L1 [mm] | 50 |
| L2 [mm] | 1 |
| ØD [mm] | 12 |
| L3 [mm] | 364 |
| R [mm] | 20 |
| P1 [mm] | 11 |
| P2 [mm] | 18 |
| A [mm] | 12 |
| M | M10 |
| d1 [mm] | 8.5 |
| d2 [mm] | 13.5 |
| B [mm] | 8.2 |
| Performance Specifications | |
| Dynamic C [N] | 14700 |
| Static C0 [N] | 13187 |
| Capacity Per Bearing [N] | 4396 |
| Weight | |
| Per Rail [g] | 6724 |