

## Prolong Bearing Assembly Reliability and Life.

Lubrication is the key to continued performance and reliability of bearing assemblies. LBL-1 is a multi-purpose pure synthetic lubricant. The stable and predictable chemical properties of LBL-1 help it

last longer and outperform conventional petroleum-based greases and oils. Lubricant additives fill microscopic surface irregularities to form a smooth, lubricated surface.



### LBL-1 LUBRICANT FEATURES AND BENEFITS

- Synthetic, non-toxic, odorless
- Low coefficient of friction
- Free flowing at down to -40°
- USDA H-1 Rating
- Water and Saltwater Resistant
- Won't drip, run or evaporate
- Inhibits rust and corrosion
- Long lasting
- Reduces friction and wear

LBL-1 SPECIFICATIONS		
ISO GRADE		220
PENETRATION (worked)		285
DROPPING POINT		N/A
GELLING AGENT		Synthetic
TIMKEN OK LOAD		40 lbs.
OIL VISCOSITY	cst @ 40°C	118-122
	cst @ 100°C	14-17
TEMPERATURE RANGE		-45° F TO 450° F

### LBL-1 4 oz. Liquid Bearing Bottle

LBL-1 LIQUID	
PART NAME	LBL-1
NET CONTENTS PER UNIT	4 oz.
PART # NLU-1006	1 BOTTLE weight of 4 oz.
PART # NLU-2006	1 CASE with 12 Bottles total weight of 3 lbs.