

NRS S 2W 44x30 w/Wipers

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your NRS S 2W 44x30 w/Wipers today!



Product Info

| | |
|---------------------------|----|
| Nominal Rod Diameter [mm] | 44 |
|---------------------------|----|

Details

| | |
|-----------|----|
| Lead [mm] | 30 |
|-----------|----|

| | |
|---|----|
| End Code for Types 1,2,3,5 [* Journals may show tracings of the thread] | 40 |
|---|----|

Dimensions

| | |
|---------|----|
| D1 [mm] | 80 |
|---------|----|

| | |
|---------|---|
| D7 [mm] | 7 |
|---------|---|

| | |
|---------|----|
| D8 [mm] | 56 |
|---------|----|

| | |
|---------|----|
| L1 [mm] | 90 |
|---------|----|

| | |
|---------|-----|
| L2 [mm] | 106 |
|---------|-----|

| | |
|--------------------|----------|
| Keyway (L x b x h) | 32x6x2.5 |
|--------------------|----------|

Performance Specifications

| | |
|---------------------------------|-------|
| Dynamic Load Ratings C_a [kN] | 80.20 |
|---------------------------------|-------|

| | |
|-----------------------------------|--------|
| Static Load Ratings C_{oa} [kN] | 103.10 |
|-----------------------------------|--------|