

PowerAC 2"-2 RA w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 2"-2 RA w/Bronze Nut today!



Rolled Inch Acme Screw

(Screw)Product Info

Screw Code	202-RA
Thread Direction	RH
Screw Material	4140 Series

(Screw)Details

Lead [in]	0.500
Starts	1
Pitch [in]	0.500
Turns Per Inch	2
Threads per Inch	2
Thread Code	202
Form	40
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	35
End Code for Type 4 [* Journals may show tracings of the thread]	19

(Screw)Dimensions

A - Root Diameter Minimum [in]	1.410
D - Nominal Rod Diameter [in]	2.000

(Screw)Part Numbers

3 ft. Part Number	11202
6 ft. Part Number	12202
12 ft. Part Number	13202
20 ft. Part Number	

(Screw)Performance Specifications

Lead Accuracy +/- [in/in]	0.0003
---------------------------	--------

(Screw)Weight

Screw Weight [lb./ft.]	8.09
------------------------	------

Inch Acme Nut with Optional Flange

(Nut)Product Info

Part Number	20202
Thread Direction	RH
Type	Bronze

(Nut)Details

Lead [in]	0.500
Starts	1
Pitch [in]	0.500
Turns Per Inch	2
Lash (Maximum Axial) [in]	0.020
Nominal Rod Diameter [in]	2.000
Threads per Inch	2
Thread Code	202
Form	40

(Nut)Dimensions

B [in]	2.75
C [in]	2.75
E [in]	0.88
F (n) Dia. [in]	(4) .531
F BCD [in]	4.062
G [in]	0.90
H [in]	4.94
J [in]	2.548-18

(Nut)Forces and Torques

Torque to Raise 1 lb. [in-lb]	0.199
-------------------------------	-------

(Nut)Flange Part Numbers

Flange No-Lash Part Number	73500
Flange Part Number	FLG7573

(Nut)Weight

Flange Weight [lb]	4.73
Nut Weight [lb]	2.87

(Nut)Performance Specifications

Efficiency [%]	40
----------------	----

Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	20000
Static Load Capacity [lb]	64000