


PowerAC 2"-4 LA w/Bronze Nut

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 2"-4 LA w/Bronze Nut today!



Rolled Inch Acme Screw

(Screw)Product Info

Screw Code	204-LA
Thread Direction	LH
Screw Material	4140 Series

(Screw)Details

Lead [in]	0.250
Starts	1
Pitch [in]	0.250
Turns Per Inch	4
Threads per Inch	4
Thread Code	204
Form	2C
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	40
End Code for Type 4 [* Journals may show tracings of the thread]	22

(Screw)Dimensions

A - Root Diameter Minimum [in]	1.694
D - Nominal Rod Diameter [in]	2.000

(Screw)Part Numbers

3 ft. Part Number	51204
6 ft. Part Number	52204
12 ft. Part Number	53204
20 ft. Part Number	

(Screw)Performance Specifications

Lead Accuracy +/- [in/in]	0.0003
---------------------------	--------

(Screw)Weight

Screw Weight [lb./ft.]	9.28
------------------------	------

Inch Acme Nut with Optional Flange

(Nut)Product Info

Part Number	80204
Thread Direction	LH
Type	Bronze

(Nut)Details

Lead [in]	0.250
Starts	1
Pitch [in]	0.250
Turns Per Inch	4
Lash (Maximum Axial) [in]	0.012
Nominal Rod Diameter [in]	2.000
Threads per Inch	4
Thread Code	204
Form	2C

(Nut)Dimensions

B [in]	3.47
C [in]	2.75
E [in]	0.88
F (n) Dia. [in]	(4) .531
F BCD [in]	4.062
G [in]	0.90
H [in]	4.94
J [in]	2.548-18

(Nut)Forces and Torques

Torque to Raise 1 lb. [in-lb]	0.166
-------------------------------	-------

(Nut)Flange Part Numbers

Flange No-Lash Part Number	73500
Flange Part Number	FLG7573

(Nut)Weight

Flange Weight [lb]	4.73
Nut Weight [lb]	2.59

(Nut)Performance Specifications

Efficiency [%]	24
----------------	----

Lead Accuracy +/- [in/in]	0.0003
Dynamic Load Capacity [lb]	20000
Static Load Capacity [lb]	64000