




## NARC 15 MS

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your NARC 15 MS today!



### Details

Size [mm] 15

### Dimensions

|                  |          |
|------------------|----------|
| W [mm]           | 34       |
| L [mm]           | 40.4     |
| L1 [mm]          | 26       |
| h2 [mm]          | 20.7     |
| P2 [mm]          | 26       |
| M1 [mm]          | -        |
| M x g2           | M4 x 7   |
| T [mm]           | 6        |
| N1               | M3 x 6.5 |
| N2               | M3 x 6   |
| N3 [O-Ring Seal] | P3       |
| E [mm]           | 4.5      |
| S1 [mm]          | 4.5      |
| S2 [mm]          | 7.5      |
| S3 [mm]          | 15.7     |
| S4 [mm]          | 16.8     |

### Forces and Torques

|                                |       |
|--------------------------------|-------|
| Basic Load Ratings C [kN]      | 7.7   |
| Basic Load Ratings C0 [kN]     | 12.1  |
| Static Moment Ratings-Ma [N-m] | 50.0  |
| Static Moment Ratings-Mb [N-m] | 50.0  |
| Static Moment Ratings-Mc [N-m] | 100.0 |

### Weight

Weight-Block [g] 96