



## Excel TEP-20

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your Excel TEP-20 today!



\* Lubrication holes for blocks up to 1/2" have flush lube fitting; 5/8" and above are 1/4" - 28 tapped hole with set screw



### Product Info

|                             |                               |
|-----------------------------|-------------------------------|
| Nominal Shaft Diameter [in] | 1 <sup>1</sup> / <sub>4</sub> |
| Part Number                 | TEP-20                        |

### Dimensions

|                 |                                 |
|-----------------|---------------------------------|
| A +/-0.001 [in] | 1.500                           |
| B [in]          | 4                               |
| C [in]          | 7 <sup>1</sup> / <sub>2</sub>   |
| D [in]          | 2 <sup>13</sup> / <sub>16</sub> |
| E +/-0.005 [in] | 3.500                           |
| F +/-0.005 [in] | 5.500                           |
| G [in]          | 3                               |
| J [in]          | 7 <sup>1</sup> / <sub>16</sub>  |
| K [in]          | 2 <sup>1</sup> / <sub>2</sub>   |
| H - Bolt        | #10                             |
| H - Hole [in]   | 0.22                            |

### Weight

|             |   |
|-------------|---|
| Weight [lb] | 5 |
|-------------|---|

### Performance Specifications

|                           |      |
|---------------------------|------|
| Dynamic Load Maximum [lb] | 2156 |
| Dynamic Load Normal [lb]  | 2034 |
| Static Load Maximum [lb]  | 1822 |
| Static Load Normal [lb]   | 1424 |