
## 

## **Product Specification Sheet**

## ActionJac 30-MSJ-UK 10 2/3:1

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your ActionJac 30-MSJ-UK 10 2/3:1 today!







415

1.750 1.760 D

2<sup>1</sup>/<sub>4</sub>-12 UN-2B

Clevis End (optional): 9001-00-08

8 - 2

 $2\frac{1}{2}$ 

|3<u>-</u>0|



## $0.1\frac{1}{16}$ 4 Holes $\frac{3}{4}$ - 2 $\frac{5}{16}$

| Details                                |                    |
|--|--------------------|
| Capacity [Ton]                         | 30                 |
| Gear Ratio                             | 10 2/3:1           |
| Turns of Worm per Inch Travel          | 16                 |
| Torque to Raise 1 lb. [in-lb]          | 0.0520             |
| Lifting Screw Diameter [in]            | 3.38               |
| Screw Lead [in]                        | 0.667              |
| Root Diameter [in]                     | 2.652              |
| Tare Drag Torque [in-lb]               | 50                 |
| Performance Specifications             |                    |
| Maximum Allowable Input [hp]           | 11.00              |
| Maximum Input Torque [in-lb]           | 2710               |
| Maximum Worm Speed at Rated Load [rpm] | 222                |
| Maximum Load at 1750 RPM [lb]          | 7618               |
| Starting Torque                        | 2 x Running Torque |
| Weight                                 |                    |
| Base 0 Travel [lb]                     | 145                |
| Per Inch of Travel [lb]                | 2.90               |
| Grease [lb]                            | 1.5                |