

148 48 48 48 48 48 48 48 4° 47 28 28 28 28 28 48 48 48 48 48 48 48 48

PowerAC 7/8"-6 TA

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your PowerAC 7/8"-6 TA today!

2D/3D CAD			
Product Info			
Screw Code		086 TA	
Screw Direction		RH/LH	
Screw Material		4140 Series	
Details			
Lead [in]		1.000	
Starts		1	
Pitch [in]		0.100	
Turns Per Inch		6	
Threads per Inch		10	
Thread Code		111	
Form		Stub	
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]		15	
End Code for Type 4 [* Journals may show tracings of the thread]		10	
Dimensions			
A - Root Diameter Minimum [in]		0.661	
D - Nominal Rod Diameter [in]		0.875	
Incomplete Overlapping Thread Length [in]		2.00	
Maximum Overall Length [in]		72	
Maximum Useable LH & RH Thread [in]		35.00	
Weight			
Weight Per Foot [lb]		2.38	
Part Numbers			
36" Part Number			
72" Part Number			
144" Part Number			
Performance Specifications		0.0000	
Lead Accuracy +/- [in/in]		0.0003	